



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

0115 Water Base Wood Putty

PROPERTIES

- Water base Wood Putty is a unique multipurpose wood and grain filler.
- It has good flexibility and bending power.
- It has good water repellence.
- It also adheres to surface with great strength.
- It is soft cutting and so levelling can be achieved easily.

APPLICATION

On wood

APPEARANCE

Butter like; easily spread able, smooth and White in colour.

BENEFITS

- Higher solid contents keep the surface smoother.
- Soft cutting and easily sand able.
- High solid contents make it less sagging.
- Good covering.

METHOD OF APPLICATION

- All surfaces to be painted should be clean from wax, loose or flake coatings, dirt, rust, grease, etc.
- Clean it with Sand Paper.
- For bigger dents over coats can be applied.
- WB Wood Putty is applied using flexible putty knife available in market.

SAFETY INFORMATION

Safety Precaution	Wear Protective clothing like overalls, gloves and goggles
Storage	Store in a cool and dry place
Shelf life	24 Months from the date of manufacturing
Disposal	Dispose in land filling. Do not dispose in any drain or water channel.