



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com, Website: www.taralac.com

0201-0202 Nc Ps Primer / Nc Filler

Introduction

Function of primer surfacer grey is to even out all minor surface defects, still left on the primered and puttied surface of a vehicle. It has ideal balance between the binder and the pigment/extenders so that it can achieve evenness on a surface and also can offer a non-absorbent finish so that subsequent coat of a finishing paint does not penetrate its film, thereby loosing gloss. The above primers contain no added lead or chromate.

Physicals constants	
Color	AS Per Shade
Finish	Smooth & Silky.
Wt. per Lt	Nearly 1.21 Kgs
Viscosity at 30°C	25 Sec by ford cup No.4 when thinned with Butyl Acetate 1:1 by volume
Flexibility	Passed 3 mm bending on bending mandrel
Sanding	Can be easily rubbed down to yield smooth & silky surface
Thinner	Taralac Solvent Mix 555\211\111

Surface Preparation

- The metal or wood surface to be coated should be free from dirt, rust, flakes, oil, grease or other loose particles.
- If previously coated, remove the coating by sanding.
- Sand the surface with emery paper no. 180.
- Followed by smooth sanding with emery paper no. 320 or 400 and cleaning of the surface to remove dust.
- Apply Taralac NC Putty Grey with Putty knife or by thinning and applying with brush.
- Smooth sand the surface with emery paper no. 180 followed by emery paper no 320 or 400 and cleaning of the surface to remove loose dust.
- Apply Taralac NC PS Grey with brush or spray to remove the minor defects on the surface.

Precautions

Avoid Skin contact. Contains volatile organic solvents.

Safety Information

Fire Hazard Class	Flammable
Safety Precaution	Wear Protective clothing like overalls, gloves and goggles
Storage	Store in a cool and dry place
Disposal	Dispose in land filling. Do not dispose in any drain or water channel.

(Covering capacity is indicated on the results obtained on normal prepared surfaces. This information is given in good faith but without warranty.)

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com, Website: www.taralac.com

Mention below the Primer and Filler Shades :-

0201 Nc Ps Grey, Nc Filler (Black / Brown)
--

0202 Nc Ps White, Nc Filler White, Grey, Redder Brown
