



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

0506 NC Lacquer Matt 15%

Products Group: Nitrocellulose Base Paint

Items: NC lacquer Matt

- Taralac NC Lacquer Clear is extensively used for polishing of wooden furniture, Anticorrosive metal coating & various industrial uses.
- NC clear lacquer is a transparent liquid & highly viscous, non-hazy & pale yellow, thereby maintaining the natural looks of the wood.
- Taralac Clear Lacquer is a high quality, quick-drying lacquer.
- It is recommended for interior wooden furniture & Metal finishes. You can use Taralac Lacquer Clear to get a Glossy, Matt or Satin finish.

Areas of Application	Metal, Interior Wooden Furniture & as a binder for various product, testing of pigments, Wooden Polish, Nail Polish, Glass Panting, Auto Refinishing etc.
Specific Gravity @30° C	0.92 – 0.98
Solids by Weight	32 – 35 %
Dilution Viscosity @27° C By Taralac Thinner 555/ Standard NC Thinner	Mixing ratio = Sample : Thinner (2 : 1) Viscosity = 50 sec – 60 sec Sample : Thinner (1 : 1) Viscosity = 25 sec – 35 sec
Gloss @ 60°	60 – 70 Unit
Method of Application	Spray or cloth rag
Spray Viscosity	18-20 sec. On Ford Cup B4 at 30°C at a pressure of 30-40 p.s.i. (2.2 to 2.8 kg / cm ²)
Recommended Thinner	Thinner 555 / Thinner 111
Covering Capacity	20-24 sq. mt. /litre per coat (85-100 sq. ft) on non pours surface such as glass or Metal depending on application and film thickness & nature of wood in case of wood.
Number of Coats	Can be recoated multiple times.
Drying time at 30°C	Touch dry 5 - 10 minutes Sanding dry 3 to 4 hours Hard dry – overnight
Recoating time	2 to 4 hours at 30°C for Clear Glossy / Matt
Flash Point	20°C
Finishes	Glossy, Matt or Satin (Smooth & Shiny surface)
Packing	200 ml, 500 ml, 1 lt, 4 lt, 20 lt, 200 lt

Note: NC Clear does not contain **LEAD OR CHROMATE** & certificate can be provided on request.

Storage:

Keep material in a cool place below 25 C. Keep the container tightly closed. **The shelf life is 24 months.**

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information

PDS Ver.No: 0506.01/12112021