

## 0525 RTU Lacquer (Optical)

- Taralac RTU Clear is extensively used as a primer for various substrates & to be overdone by Hydrographic
- It has a good levelling as well as filling property & it offers good adhesion & fast dry properties.
- RTU clear is transparent liquid & ready to use, non-hazy & pale yellow, thereby maintaining the natural looks of the substrate

|                              |                                                                                                                                                                         |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Areas of Application</b>  | As a primer for hydrographic                                                                                                                                            |
| <b>Method of Application</b> | Spray, Brush or cloth rag                                                                                                                                               |
| <b>Spray Viscosity</b>       | 18-20 sec. On Ford Cup B4 at 30°C at a pressure of 30-40 p.s.i. (2.2 to 2.8 kg / cm <sup>2</sup> )                                                                      |
| <b>Recommended Thinner</b>   | Solvent Mix 555 or Solvent Mix 111                                                                                                                                      |
| <b>Covering Capacity</b>     | 20-24 sq. mt. /litre per coat (85-100 sq. ft) on non pours surface such as glass or Metal depending on application and film thickness & nature of wood in case of wood. |
| <b>Number of Coats</b>       | Can be recoated multiple times.                                                                                                                                         |
| <b>Drying time at 30°C</b>   | Touch dry 5 - 10 minutes<br>Sanding dry 3 to 4 hours<br>Hard dry – overnight                                                                                            |
| <b>Flash Point</b>           | 17 °C                                                                                                                                                                   |
| <b>Finishes</b>              | Smooth & Shiny surface                                                                                                                                                  |
| <b>Packing</b>               | 1 lt, 4 lt, 20 lt, 200 lt                                                                                                                                               |

**Note:** NC Sanding sealer, NC Clear does not contain **LEAD OR CHROMATE** & certificate can be provided on request.



**TARALAC®**

# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com



**TARALAC®**