



# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: [taralac@hotmail.com](mailto:taralac@hotmail.com) , [taralac@taralac.com](mailto:taralac@taralac.com) Website: [www.taralac.com](http://www.taralac.com)

## **0706 PU Int Matt Black (2:1)**

### **Safety Data Sheet**

#### **SECTION 1- IDENTIFICATION OF THE MATERIAL AND SUPPLIER**

- 1.1 Product Name: Two Pack Polyurethane Paints with iso-cynate hardener  
1.2 Manufacturers product code: various  
1.3 Uses: Industrial Paint (Spraying)  
1.4 Tara Paints And Chemicals  
A/423/14, Mahagujarat Ind. Estate,  
Sarkhej-Bavla Road,  
NH.No.8A, Moraiya,  
Ahmedabad- 382210  
Emergency Telephone: 02717-320003

#### **SECTION 2- COMPOSITION/ INFORMATION ON INGREDIENTS**

##### **2.1 Ingredients**

| Chemical Entity              | Cas no     | Weight | Hazard Symbols | EU Risk Phrases |
|------------------------------|------------|--------|----------------|-----------------|
| Xylene                       | 133020-7   | 10-30% | Xn, Xi         | R20/21,R38      |
| n-Butyl Acetate              | 123-86-4   | 10-30% |                |                 |
| Aromatic Hydrocarbon Mixture | 64742-95-6 | 1-10%  | Xn, Xi         | R66,R67,R51/53  |
| Methoxy Propyl Acetate       | 108-65-6   | 1-10%  | Xi             | R36             |

Ingredients determined to be non hazardous TO 100%  
Or Below the hazardous threshold

#### **Section 3- HAZARDS IDENTIFICATION**

R20/21

3.1 Hazardous substance dangerous goods

3.2 Risk Phrases R20/21 Harmful by inhalation in contact with skin.

3.3 Safety Phrases S16 Keep away from sources of ignition No Smoking.  
S57 Use appropriate container to avoid environmental Contamination.

This material and/or its container must be disposed of as S60 Hazardous waste.

#### **SECTION4- FIRST AID MEASURES**

##### **4.1 First Aid**

**Swallowed:** Do not induce vomiting give 250 ml water to drink. Seek immediate medical attention.

**Eye Contact:** Immediately flush eyes with water for at least 15 minutes. Seek medical attention.

**Skin Contact:** Wash thoroughly with soap and water. If irritation still present, seek medical attention.

**Inhaled:** Remove to fresh air, rest. If breathing is difficult, give artificial respiration.

##### **4.2 Advice to Doctor**

Treat symptomatically.



# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: [taralac@hotmail.com](mailto:taralac@hotmail.com) , [taralac@taralac.com](mailto:taralac@taralac.com) Website: [www.taralac.com](http://www.taralac.com)

## SECTION 5- FIRE FIGHTING MEASURES

### 5.1 Fire/Explosion Hazard

Flammable liquid. Vapours form explosive mixture with air (see limits in section 9)

extinguishing Media: Foam, Dry Powder, CO<sub>2</sub>, Water Fog. Do not use water except as fog to cool nearby containers. Wear breathing apparatus when fighting fire. Decomposition Products: Oxides of Carbon, and possibly other noxious products.

### 5.2 Hazchem Code 3[Y]E

## SECTION 6- ACCIDENTAL RELEASE MEASURES

### 6.1 Spills

Minor- Extinguish naked flames. And avoid sparks. Absorb with sand, sawdust or earth. Collect in drums, and arrange for disposal by a competent contractor, in accordance with local regulations. Major-Extinguish naked flames and avoid sparks. Wear appropriate protective clothing and equipment. Evacuate surrounding personal. Dike area of spill, and transfer to empty drums. Residue to be absorbed with sand, sawdust or earth, and placed in drums. Arrange disposal by competent contractor. In accordance with local regulations.

## SECTION 7- HANDLING AND STORAGE

### 7.1

Avoid sources of heat, naked flames and sparks. Use in well ventilated area. Use flame proof equipment. Earth all containers to reduce the possibility of sparks from static electricity. Store in a cool, well ventilated place away from heat, naked flames and sparks. Store away from oxidizing agents, alkaline materials and strong acids. Keep container closed at all times. Keep away from food, and drink and clothing.

## SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Exposure Standards

| Chemical Entity              | Cas No   | Weight%    | TLV/TWA | Stel   |
|------------------------------|----------|------------|---------|--------|
| XYENE                        |          | 1330-20-7  | 10-30%  | 50pm   |
| N-BUTYL ACETATE              | 123-86-4 | 10-30%     | 150 PPM | 200PPM |
| AROMATIC HYDROCARBON MIXTURE |          | 64742-95-6 | 1-10%   | 19PPM  |
| ISO-BUTYL ALCOHOL            | 78-83-1  | 1-10%      | 50PPM   |        |
| METHOXY PROPYL ACETATE       |          | 108-65-6   | 1-10%   | 100PPM |

### 8.2 ENGINEERING CONTROLS

General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below TLV. Ventilation equipment should be explosion proof.

### 8.3 PERSONAL PROTECTION

Wear chemical safety glasses/goggles or face shield. Wear half face respirator, with organic vapour cartridge. Wear PVC or Nitrile chemical handling gloves.

## SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 PHYSICAL DESCRIPTION/PROPERTIES

Appearance Coloured Liquid, Solvent Odour.



# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: [taralac@hotmail.com](mailto:taralac@hotmail.com) , [taralac@taralac.com](mailto:taralac@taralac.com) Website: [www.taralac.com](http://www.taralac.com)

Boiling Point 118 deg C  
Specific Gravity 1.23  
Flash Point 20 deg C  
Flammability Limits 1-8% by volume in air  
Volatile content 42.1% by weight  
Solubility in water Low

## SECTION 10- STABILITY AND REACTIVITY

10.1  
Normally stable.

## SECTION 11- TOXICOLOGICAL INFORMATION

### 11.1 HEALTH EFFECTS

Swallowed

Slightly toxic. Main hazard of ingestion is aspiration of swallowed liquid into lungs, causing chemical pneumonitis.

Eye Contact Irritating, causing redness and burning sensation.

Skin Contact Irritating, causing redness and burning sensation.

Inhaled Harmful by inhalation. The vapour is irritating to the upper respiratory tract.

May cause nausea, dizziness and narcosis. Extreme exposure may result in unconsciousness, and possibly death.

Chronic or Other Prolonged and repeated contact with the skin may irritate, and cause dermatitis.

Prolonged overexposure to the solvents ( inhalation and skin contact) may cause effects to the central nervous system, liver, urinary, blood forming, cardiovascular and reproductive systems. See section 3.2 for other chronic health risks.

### 11.2 TOXICITY OF INGREDIENTS

| Chemical Entity              | Weight % | LD50 Oral Rat mg/kg | LD Dermal Rat or Rabbit mg/kg | LC50 Inhalation Rat Mg/L4hr |
|------------------------------|----------|---------------------|-------------------------------|-----------------------------|
| XYLENE                       | 10-30%   | >2000               | >2000                         | >5                          |
| N-BUTYL ACETATE              | 10-30%   | 6500                | >2000                         |                             |
| AROMATIC HYDROCARBON MIXTURE | 1-10%    | >2000               | >2000                         |                             |
| ISO-BUTYL ALCOHOL            | 1-10%    | 2460                | 4240                          | 8000                        |
| METHOXY PROPYL ACETATE       | 1-10%    | >5155               | >2000                         | >37500                      |

## SECTION 12- ECOLOGICAL INFORMATION

### 12.1 NOHAC Risk Phrases R52/53

Harmful to aquatic organisms, may cause long term adverse effects in the aquatic environment.

## SECTION 13- DISPOSAL CONSIDERATIONS

### 13.1

Do not let this product enter the environment. Dispose of this material and its container as hazardous waste. Do not pour unwanted paint or paint-related material down the drain. Keep unwanted material in sealed containers for disposal via special chemical waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle steel



# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: [taralac@hotmail.com](mailto:taralac@hotmail.com) , [taralac@taralac.com](mailto:taralac@taralac.com) Website: [www.taralac.com](http://www.taralac.com)

containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities check with your local council first.

## SECTION 14- TRANSPORT INFORMATION

14.1 Packing Group: 11 Hazchem Code: 3[Y] E

## SECTION 15-REGULATORY INFORMATION

15.1 SUSDP SCHEDULE Not Applicable

15.2 HMIS CODE 230H

## SECTION 16- OTHER INFORMATION

16.1 When sanding any, paint use wet sanding to avoid breathing dust. Wear a dust respirator if wet sanding not possible. Refer to the Technical Data Sheet for this product for directions for use.

16.2

Packaging and Signal Words HAZARDOUS

Labelling Cautionary Statements:

Flammability: Highly Flammable

Hazard Symbols: Xn

R&S Phrases: Refer to Section 3

Labeled Ingredients: Xylene 15-20%