



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade, Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com, taralac@taralac.com Website: www.taralac.com

0720 Isolant Primer (sp)

TYPE	Based on Modified Resin.
FEATURES	Two-pack system, Base & Hardener Packed & supplied separately to mix just before use. This Primer has excellent resistance to moisture & chemicals and excellent adhesion on wood and MDF. It has good leveling & durability. Also work as barrier coat on wood
RECOMMENDED USE	On Wood and MDF
PRODUCT DATA	
COLOURS	Transparent
SPECIFIC GRAVITY	0.96 $\pm$ 0.03
VISCOSITY	50 $\pm$ 10 Seconds by Flow Cup No.4 at 30°C
FINISH	Smooth, Uniform, free from Sagging & Wrinkling
DRYING	Surface Dry: 30 Minutes max Sandability: After 1 Hour.
FLASH POINT	Above 20°C
APPLICATION DATA	
APPLICATION	By Spray at 25-30 seconds viscosity
THINNER	PU AUTO Thinner
MIXING RATIO (BY VOLUME)	Base : Hardener (1:1)
POT LIFE (OF MIXTURE)	1 - 3 Hours
MATURATION TIME	10 to 15 Minutes
THEORETICAL SPREADING RATE	5-7 Sq.M/Ltr. Per coat at 15-20 μ D.F.T.
CHEMICAL RESISTANCE	
SHELF LIFE	6 months in sealed containers separately packed at normal ambient temperature.
PACKING	1 Ltr. And 2 Ltr.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information

PDS Ver.No.: 0720.01/29112021