



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

1401 Syn DC Aluminium Paint

TARALAC Aluminium Paint is two-pack synthetic resins based aluminium paint. It has very good adhesion, durability and flexibility. It is suitable for surfaces susceptible to atmospheric corrosion and in environments where good durability is required. Good heat-resisting properties and high covering capacity coupled with long life make this paint the most desired coating from the point of view of economy and performance. This paint is widely used for steel structures such as railway wagons, bridges, electrical transmission towers, oil tanks, gates and fences.

TECHNICAL DATA

Areas of application	Steel structures, wagons, oil tanks etc
Supply Viscosity of medium	15 to 20 Seconds by ford cup B4 at 30° C
Thinner recommended	Taralac St Thinner ST – 2
Method of application	Brushing or Spraying
Drying time	Surface Dry: Less than 3½ hours Hard Dry: Overnight
Finish	Lustrous
Covering capacity (Spreading by brushing on smooth non-absorbent surface)	8 - 10 sq. Mts./ltr/coat depending upon the nature of the substrate at 20 - 25 microns film thickness
Flash Point	Above 30° C (86° F)
Packing Available	20 Ltrs

DIRECTIONS FOR USE:

Surface Preparation & Substrate Condition:

The surface should be free dirt, dust, grease, rust, moisture etc. Recommended methods for steel are by Sa2½ sandblasting or with the help of wire brush.

Mixing:

Mix the entire quantity of supplied Aluminium paste thoroughly with a small quantity of medium and then add the mixture to the remaining medium. Stir well before use.

Mixing Ratio : **Medium: Aluminium Paste**
(By weight) 86 : 14

Pot life : Not applicable

NOTE:

For best results, use the mixed paint within 6 hours of mixing. The larger period will reduce the lustre of the paint.