

1411 Syn Chasis Red / Glossy Red Oxide

Syn Enamel Paint is a Single Pack First Quality Hi-Gloss Alkyd Enamel Paint, used multi-purposely on various substrates.

ADVANTAGES:

- For interior and exterior surfaces like masonry, steel, wood, asbestos etc.
- Weather resistance and exterior protection.
- Good colour retention.
- Ease of application.
- Excellent for wood and metal surfaces.
- Good hiding power and adhesion.
- Super glossy finish.

TECHNICAL DATA

Areas of application	Wood, Asbestos, masonry, Metal etc.
Thinner recommended	Taralac St Thinner ST - 2
Method of application	Brushing or Spraying
Drying time	Surface dry - 1 - 2 hr Hard dry - less than 18 hours
Viscosity	70 - 80 sec
Volume Solids	Approx 48 - 58%
Specific Graviry	0.90 - 1.15 kg/ltr
Finish	Smooth and Glossy
Covering capacity	18 - 24 sq. Mts./ltr/coat depending
(spreading by brushing on smooth non-absorbent surface)	upon the nature of the substrate at 20 - 25 microns film thickness
Flash Point	Above 30° C (86° F)
Shade Available	Various
Shelf Life	One Year
Packing Available	20 Ltrs., 4 Ltrs., 1 Ltrs., 500 ml., 200 ml.,

APPLICATION PROCEDURE:

- The substrate must be free from oil and other contaminants.
- Sandblasting is required to Sa 2 ½, if sandblasting is not possible, manual wire brushing is recommended. Use Paint Remover to remove away rust and rinse with water and let it dry. Apply 1- 2 coats of red oxide primer by roller, brush or spray or 1 - 2 coats of undercoat before the application of HI - GLOSS ENAMEL.