



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

1901 Plastic Primer / Adhesion Promotor

DESCRIPTION

Plastic Adhesion Promoter is a fast, transparent 1 Pack primer suitable for use on the vast majority of paintable plastic substrate avoiding the need to identify the plastic prior to spraying.

FEATURES

- Superior bonding properties
- Topcoat with most refinish products
- Excellent on olefin based plastics
- Easy to apply

SUITABLE SUBSTRATES

- Olefin-based plastics

Sp. Gravity	0.876
Flash Point	Closed cup: 24C
Volume Solids	4
Finish	Matt
Colour	Clear

HANDLING AND APPLICATION:

PREPARATION:

1. Clean area with SEM Soap (interior plastics) or Scuff & Clean (exterior plastics) and a gray scuff pad.
2. Rinse with water and allow to dry.
3. Next, clean with Plastic & Leather Prep or Zero VOC Surface Cleaner using a clean, lint free towel and wiping in one direction.

APPLICATION:

1. Apply one light coat.
2. Allow 5 minutes flash time followed by one full wet coat.
3. Allow to flash 15 minutes but no longer than 30 minutes before top-coating.
4. Refinish with Colour Coat, Bumper Coater, Marine Vinyl Coat, Marine Engine Paint, all base coats, clear coats, urethanes, acrylic enamels, alkyd enamels and acrylic lacquers.

STORAGE:

Plastic Adhesion Promoter should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for Plastic Adhesion Promoter is 5 years when stored under normal conditions.