



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

1906 Degreasing Solvent

DESCRIPTION

Degreasing Solvent is a versatile, chlorinated solvent-based degreaser that is extremely effective in most heavy duty applications. It aggressively dissolves grease, oil and sludge for more efficient operation of mechanical equipment.

Degreasing Solvent evaporates quickly, and is non-conductive, non-corrosive, and non-staining.

Degreasing Solvent dries residue free for quick and easy maintenance of industrial and electrical equipment.

FEATURES

- **No Flash or Fire Point.** Significantly reduces the risk of fire caused by incidental contact with live electrical equipment or solvents trapped by insulating materials.
- **Fast Evaporation.** Minimizes downtime associated with “clean-in-place” cleaning methods.

APPLICATIONS

Recommended for the effective removal of grease, oil, corrosion and sludge from air tools, mechanical brakes, clutches, chains, wire ropes, motors, dies, molds, parts, bearings, generators and compressors.

Sp. Gravity	0.97
Flash Point	Closed cup: 40 C
Colour	Clear
Solubility	Slight in water

Directions

- Remove mechanical plates, covers, etc. to expose equipment interior. For best results, remove heavy deposits of contaminants by scraping with a knife or wire brush.
- Spray liberally and allow to run off or apply by brush or cloth rag
- Use extension tube for hard-to-reach areas.
- Allow equipment to fully dry and vent before using.
- Scrub the applied area with cloth rag or scrub.
- Do not use on plastics such as acrylic, ABS and polycarbonate. If uncertain, check with the manufacturer or test on a small area before using.
- Not for use on sensitive electronics, computers, tape decks or VCRs.
- For personal safety, do not use while equipment is energized

Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.