



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

2205 Laccolite Clear

Introduction:

The varnish is dark coloured but with very good flexibility, high bonding strength, good surface built up, An anticorrosive & waterproofing paint, having one of the best, cheapest & easy applicability. It is required for the following properties:

- Anticorrosive properties.
- Acid & Alkali Resistance
- Termite resistance
- High adhesion to any kind of substrate.

TECHNICAL DATA

Uses	Metal, Masonry & Wood etc.
Thinner	Taralac Syn. Thinner ST – 2
Method of application	Brushing, Spraying or dipping
Sp.Gr. at 27° C	0.90 to 1.0 gm/cm ³
Covering capacity	10 - 14 sq. Mts./lt/coat depending on the porosity of the surface and
(Spreading by brushing on smooth Non-absorbent surface)	Upon the nature of substrate at 20 - 25 microns film thickness on the non-adsorbent surface
Flash Point	Above 60° C
Shade Available	Dark Varnish
Packing Available	200lt, 20lt, 4lt, 1lt, 500 ml, 200 ml.
Ductility at 27° C	2 or more than 2
Areas of Application	<ul style="list-style-type: none">• On TMT bars used for construction• For waterproofing, Damp Proofing, Mastic asphalt for roads & floors, Foam Concreting. On terrace floors or to fill cracks.• On any metal surface (pipes, bars, etc.)• On old painted surfaces.• Over brick masonry & Concrete.• Thick Coat As a Sound Proofing• Before wooden Paneling

Directions for use:

Ensure that the surface to be painted is free from loose matter, dust etc.

Apply a coat of paint by brushing after adjusting consistency using the recommended thinner. It can also be applied by spray applications.

(The information in this leaflet is given in good faith but without warranty. Covering capacity is indicated on the Basis of results obtained on a prepared smooth surface.)

Note:

The container should be stored in tight lid, under the shed.
Should not be exposed to naked flames.