



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@taralac.com Website: www.taralac.com

3703 Super Interio Wall Primer (Int)

Tara Paint SUPER INTERIOR WALL PRIMER

Tara Paint SUPER INTERIOR WALL PRIMER water based wall A primer especially designed for the binding of loosely bound, powdery and chalking surfaces. Recommended for use when redecorating external walls which have been neglected and wall and ceiling surfaces previously coated with cement paints, distemper, lime wash etc. The application of emulsion and other pigmented finishes directly onto loosely bound surfaces invariably results in an early breakdown due to loss of adhesion. Prior to the application of TARALAC Penetrating Primer, all loose, unsound and flaking paint and other contamination must be removed

PRODUCT BENEFIT

- Easy brushing. Excellent covering,
- Excellent opacity and whiteness. Improve appearance of topcoat
- Alkali resistance. Quick drying and good sealing properties.
- It specially containing with fungicides,

PRODUCT FEATURE

Shelf Life	3 year from date of manufacturing in original tightly closed containers away from direct sunlight and excess heat.
Colour available	White undercoat
Coverage	On smooth masonry surface by brushing 120-140 sq./ltr
Drying time to Touch	1 hrs
Recommended Usages	It can be used for priming plastered walls, asbestos, brick work, concretes etc.

How to Apply

PLASTER New Masonry Surface must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

CLEANING: - Surface should be free from all dirt, loosely held plaster, Powdery residue, oil, grease or any other any loose paint dust or grease or any other contamination. Any previous growth of fungus, algae, or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water. One coat of biocidal solution is recommended to prevent further growth of algae, fungus, or moss.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@taralac.com Website: www.taralac.com

REPARING: -The Substrates must be checked for its soundness using small hammers. All cracks at corner joints, channels and parapets should be properly treated.

FILLING FOR CRACKS: -For filling cracks up to 3 mm use Crack Filler. Bigger crack, damaged portion and hallow areas must be repaired with polymer modified cement mortars.

POST PAINTING CARE: -For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth, if any at regular interval of six month.

TECHNICAL DETAILS: -

PRODUCT	THINNER	DILUTION %[BY VOL]	APPLICATION VIS[SEC]	RECOATING PERIOD [HOURS]
Wall Putty	Water	As Per Requirement to form paste	Paste form	4
TARALAC Paint wall primer Brush Spray	Water	80-100 35-40	15-18 33	4

TITLE	DETAILS
Coverage	On normal masonry surface by brushing 1 coat: 6 to 7 sq meter/litter on smooth surface
Drying Time	Surface Dry time-30 minutes
Density	0.90+-0.10 weight/litter
Sheet Time	NA
Stability of Thinned Paint	Use within 24 hours
Shelf-Life	18 months from date of manufacturing in original toughly closed containers away from direct sunlight and excessive heat.

PRECAUTION

Do not apply during rains or extremes temperatures.

Do not over thin or over extend the brush. Avoid Abuse which may lead to puncturing of membrane

Stir well and strain before use

In coastal area, it's not recommended to leave the primer without the application of topcoat for long period of time.

SAFETY FEATURES

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@taralac.com Website: www.taralac.com

Kindly refer to the MSDS of TARA PAINTS SUPER INTERIOR WALL PRIMER which gives detailed information on safety measures while handling the paints, which is available on request.

Store the containers with the lid tightly closed in an upright position, in a cool dry place

Keep out of reach of children and away from eatables.

May be harmful if swallowed in case of ingestion seek immediate medical attention.

Wear eye protection during application. In case of contact with eyes, rinse immediate with plenty of water and seek medical advice.

In case of skin contacts immediately wash Skin with soap and plenty of water. Get medical attention if irritation develop or persists.

Do not breathe vapors or spray .it is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses

In event of the spills contain spillage using hand or earth

No added lead, mercury, or Chromium compounds.



TARALAC®