



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

3716 Classic Acrylic Distemper

TARALAC Classic Acrylic Distemper is water based interior wall paints .It is value for money products that makes it possible for consumers to have beautiful walls at affordable price. It has on an exquisite collection of pastel shade and refreshing range of tinted whites inspires by mother nature they set the right mood to your home besides giving your walls the sheen and finish of silk.

PRODUCT BENEFITS

Classic Acrylic Distemper offers a smooth, matt finish, yours walls looks like new for a longer time as the shades retains their brightness.

Wash ability you can clean your stains with a wet cloth.

Color It Available in a wide ranges of shades .Thus you can choose your favorites colors for your walls.

PRODUCTS FEATURES

Wash ability medium

Available packs 1 kg, 2 kg, 5 kg, 10 kg, and 20 kg

Available in 950 shades

Technical Details:

TITLE	DETAILS
Areas of Application	Interior Plaster, Brick Work, Asbestos
Consistency Offered	64+2Ps Rot thinner At30°C
Density	1.6 to 1.8 weight/litter
Thinner	Municipal/Portable Water
Method of Application	Brush or Roller
Covering Capacity	16-17 Sq. meter/Kg/Coat
[Spreading by Brushing]	7-9 Sq. meter/Kg/2 Coats (Depending upon the shade, the surface and surface Preparation.)
Primer Recommended	Classic Cement Primer (Solvent Thinnable or Water Thinnable)
Drying Time	Surface Dry Maximum 30 Minutes [@28-30°C & 60±5% R.H]
Recoating Period	3 to 4 hours
Finish	Smooth and Matt
Shades Available	As per Shade Card

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

Packs Available

20kg, 10kg, 5kg, 4kg, 2kg, 1kg

POST PAINTING CARE

For removing stains, wipe clean with a wet cloth, Ensure a drying time of minimum 2 weeks from application. before cleaning.

PRECATUTIONS

Do not apply when ambient temperature is less than 10 degree if the temp might drop to this level within

4 hrs of application.

Donot over thin or over –extend the brush.

Tint using machine colorant only.

Stir well and strain before use.

Tinted paints need through shaking immediately after tinter addition as well as before use.

SAFETY FEATURES

Kindly refer the MSDS from TARA PAINTS Classic Acrylic Distemper which gives detailed information on safety measure while handling the paints which is available on request.

Store the containers with the lid tightly closed in an upright position, in a cool and dry place.

Keep out of reach of children and away from eatables

May be harmful if swallowed in case of ingestion seek immediate medical attention

Wear eye protection during application .In case of contact with eyes rinse immediately with plenty of water and seek medical advice.

In case of skin contacts immediately wash skin with soap and plenty of water .Get medical attention if irritation develops or persists

Do not breathe vapors or spray .It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses

In the event of spills, contain spillages using sand or earth

No added lead, mercury, and chromium compounds.