



**TARALAC®**

# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: [taralac@hotmail.com](mailto:taralac@hotmail.com) , [taralac@taralac.com](mailto:taralac@taralac.com) Website: [www.taralac.com](http://www.taralac.com)

## **3731 Classic Interior Emulsion**

TARALAC CLASSIC INTERIOR EMULSION is water-based, modified acrylic exterior wall finish with silicon additives for use in dry to moderately humid climatic conditions.

### **Performance Features & Benefits:**

TARALAC CLASSIC INTERIOR EMULSION offers excellent resistance to chalking, cracking and weathering in comparison to cement Paints this product gives cleaner shades which do not fade the last longer, it offers good anti algal performance in dry to moderately humid climatic conditions. However, it may not completely prevent the growth of black algal spot in excessive rainfall area/coastal belts.

### **Recommended Usage:**

TARALAC CLASSIC INTERIOR EMULSION is an exterior wall finish that can be applied on all exterior cement plasters, exterior ceilings asbestos sheets, concrete etc.

The product cannot be applied on roof tiles and on surface/substrates that are subjected to continuous seepage and dampness.

### **Surface Preparation:**

Freshly Plastered Surfaces: This must be allowed to cure completely.

Cleaning: Ensure that the surface to be painted is free any loose paints, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous, wire brushing and cleaning with water.

### **Filling:**

Surface imperfections such as holes, dents, fine and cracks are to be filled using wall putty or a mixture of white cement and fine sand [in ration 1:2]

### **Technical Details:**

PRODUCT	THINNER	DILUTION %[BY VOL]	APPLICATION VIS[SEC]	RECOATING PERIOD [HRS]
Wall Putty	Water	As Per Requirement to form a paste	Paste form	4
TARALAC Paint wall primer Brush Spray	Water	90-110 40-45	15-18 33	4

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information



**TARALAC®**

# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: [taralac@hotmail.com](mailto:taralac@hotmail.com) , [taralac@taralac.com](mailto:taralac@taralac.com) Website: [www.taralac.com](http://www.taralac.com)

TARALAC Paints Exterior Emulsion 1st coat Brush, Spray	Water	MAX 75	20-25 20-25	4-6
TARALAC Paints Exterior Emulsion 2nd coat Brush, Spray	Water	MAX 75	20-25 20-25	4-6

TITLE	DETAILS
<b>Coverage</b>	On normal masonry surface by brushing 1 coat:10-12sq mtr/ltr 2 coat : 5-6 sq./mtr
<b>Drying Time</b>	Surface Dry time-30 minutes
<b>Sheen levels</b>	1-6 at 60 Deg GH
<b>Stability of Thinned Paint</b>	Use within 24 hrs
<b>Shelf-Life</b>	18 months from date of manufacturing in original toughly closed containers away from direct sunlight and excessive heat.
<b>Precautions</b>	Do not apply when the ambient temperature is less than 10 C or if the temperature might drop to this level within 4 hrs of application. Do not over thin or overextend the brush. Do Not use any other colourants.
	Ensure that horizontal surface like the top of windows, ledges etc. are painted with 3 coats for greater protection.
	Tinted paints need through shaking immediately after tinted addition as well as before use.
	Excessive bird droppings/spitting may affect the performance of the product.
<b>Post Application instruction</b>	For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth at regular intervals of six months.
<b>Safety Features</b>	Non- Flammable
<b>Packs Available</b>	1ltr, 4ltr,5ltr,10ltr,20ltr

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information