



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

3732 Glow Exterior Emulsion

TARALAC Glow Exterior Emulsion is water-based, modified acrylic exterior wall finish that impart a hi-sheen finish to the exterior wall for use in dry to moderately humid climatic conditions.

Performance Features & Benefits:

TARALAC Glow Exterior Emulsion offers excellent resistance to chalking, cracking and weathering in comparison to cement paints.its modified acrylic binder ensures that paint stays on your wall longer than cement paints. Glow gives cleaner shades which do not fade the last longer, Glow offers good anti algal performance in dry to moderately humid climatic conditions. Glow comes with a compressive 3 year performance warranty which can be attributed to its best in class film integrity and lower moisture absorption by virtue of its water resistance technology. Best in class product it available in 1050 shades.

Recommended Usage:

TARALAC Glow Exterior Emulsion is an exterior wall finish that can be applied on all exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. The product cannot be applied on roof tiles and on surfaces/ substrates that are subjected to continuous seepage and dampness.

Surface Preparation:

Freshly plastered Surface: This must allow curing completely.

Cleaning:

Ensure that the surface to be painted is free any loose paints, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous, wire brushing and cleaning with water.

Filling:

Surface imperfections such as holes, dents, fine cracks are to be filled using wall putty or a mixture of white cement and fine sand [in the ratio 1:2].

Technical Details:

PRODUCT	THINNER	DILUTION %[BY VOL]	APPLICATION VIS[SEC]	RECOATING PERIOD [HRS]
Wall Putty	Water	As Per Requirement to form a paste	Paste form	4
TARALAC Marvel exterior wall primer Brush Spray	Water	90-110 40-45	15-18 33	4
TARALAC Glow Exterior Emulsion 1st coat Brush, Spray	Water	MAX 75 MAX 75	20-25 20-25	4-6
TARALAC Glow Exterior Emulsion 2nd coat Brush, Spray	Water	MAX 75 MAX 75	20-25 20-25	4-6

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

TITLE	DETAILS
Coverage	On normal masonry surface by brushing 1 coat:10-12sq mtr/ltr 2 coat : 5-6 sq./mtr
Drying Time	Surface Dry time-30 minutes
Sheen levels	1-6 at 60 Deg GH
Stability of Thinned Paint	Use within 24 hrs
Shelf-Life	3 Years from date of manufacturing in original toughly closed containers away from direct sunlight and excessive heat.
Precautions	Do not apply when the ambient temperature is less than 10 C or if the temperature might drop to this level within 4 hrs of application. Do not over thin or overextend the brush. Do Not use any other colourants.
	Ensure that horizontal surface like the top of windows, ledges etc. are painted with 3 coats for greater protection.
	Tinted paints need through shaking immediately after tinted addition as well as before use.
	Excessive bird droppings/spitting may affect the performance of the product.
Post Application instruction	For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth at regular intervals of six months.
Safety Features	Non- Flammable
Packs Available	1ltr, 4ltr,10ltr,20ltr

Surface Preparation:

Cleaning Ensure that the surface to be painted is free from any loose paints dust or grease. Any previous growth of fungus algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.

Filling:

Application of any kind of Putty is not recommended surface imperfections such as holes, dents and fine cracks are to be filled only by using a mixture of white cement and fine send [in the ratio 1:2].

POST PAINTING CARE

For the best performance of paint, ensure proper washing and cleaning of all algal and fungal growth if any at regular interval of six months.

PRECAUTIONS

Do not apply when ambient temperature is less than 10degree or if the temperature might drop to this level within 4 hrs of application. Donot over thin or over extend the brush. Tint using Tara paints machine colorant only.

Stir well and strain before use.Tinted paints needs through shaking immediate after tinter addition as well as before use.

SAFETY FEATURES

Kindly refer to the MSDS for TARA PAINTS MARVEL exterior emulsion paints which gives detailed information on safety measures while handling the paint.

Stores the containers with the lid tightly closed in upright position in a cool

Keep away from children.

In case of eye/skin contact, wash with plenty of water.

Inhalation/Injection is dangerous, In either case move to fresh air and consult a medical practitioners

Do not apply when ambient temp might drop to a level below 10 degree within 4 hrs. of application

New plaster should be allowed to cure for minimum 12 weeks.

Avoid extra thinning for better results.

Containers must be tightly closed when not in use .Stir well and strain before use.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

Use safety equipment like rubber or polyethylene gloves, safety goggles /glasses & face mask.



TARALAC®