



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

3735 Marvel Plus Weather Proof Ext Emulsion

TARALAC MARVEL PLUS W/E is water-based, modified acrylic exterior wall finish with silicon additives.

Performance Features & Benefits:

TARALAC MARVEL PLUS W/E is a high performance, long-lasting exterior paint specially formulated to withstand extreme tropical condition of high rainfall, humidity and heat marvel plus provides excellent resistance against the growth of algae and fungi on the wall. Marvel plus offers excellent protection against alkali and UV degradation.

Recommended Usage:

TARALAC MARVEL PLUS W/E is an exterior wall finish that can be applied on all exterior cement plasters, exterior ceilings, asbestos sheets, concrete etc. The product cannot be applied on roof tiles and on surfaces/ substrates that are subjected to continuous seepage and dampness.

Surface Preparation:

Freshly plastered Surface: This must allow curing completely.

Cleaning:

Ensure that the surface to be painted is free any loose paints, dust or grease. Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous, wire brushing and cleaning with water.

Filling:

Surface imperfections such as holes, dents, fine cracks are to be filled using wall putty or a mixture of white cement and fine sand [in the ratio 1:2].

Technical Details:

PRODUCT	THINNER	DILUTION % [BY VOL]	APPLICATION VIS [SEC]	RECOATING PERIOD [HRS]
Wall Putty	Water	As Per Requirement to form a paste	Paste form	4
TARALAC Marvel exterior wall primer Brush Spray	Water	90-110 40-45	15-18 33	4
TARALAC Marvel PLUS W/E 1st coat Brush, Spray	Water	MAX 40 MAX 40	20-25 20-25	4-6
TARALAC MARVEL PLUS W/E 2nd coat Brush, Spray	Water	MAX 40 MAX 40	20-25 20-25	4-6

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information



TARALAC®

TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

TITLE	DETAILS
Coverage	On normal masonry surface by brushing 1 coat:10-12sq mtr/ltr 2 coat : 5-6 sq./mtr
Drying Time	Surface Dry time-30 minutes
Sheen levels	2-8 at 60 Deg GH
Stability of Thinned Paint	Use within 24 hrs
Shelf-Life	3 Years from date of manufacturing in original toughly closed containers away from direct sunlight and excessive heat.
Precautions	Do not apply when the ambient temperature is less than 10 C or if the temperature might drop to this level within 4 hrs of application. Do not over thin or overextend the brush. Do Not use any other colourants. Ensure that horizontal surface like the top of windows, ledges etc. are painted with 3 coats for greater protection. Tinted paints need through shaking immediately after tinted addition as well as before use. Excessive bird droppings/spitting may affect the performance of the product.
Post Application instruction	For the best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth at regular intervals of six months.
Safety Features	Non- Flammable
Packs Available	1ltr, 4ltr,5ltr,10ltr,20ltr

TARALAC®